



Cognito Motorsports, Inc. Factory Skid Plate Mount for 2014-Current GM 2WD & 4WD 6 Lug Trucks and SUV's

Before starting the installation process please find the appropriate parts breakdown and check off each part to ensure your kit is complete

Parts Breakdown

FSPA-2014		
Part #	Qty	Description
8436	1	Skid Plate Mounting Bracket
HP9162	1	Bracket Hardware

Introduction

- Read instructions carefully and study the pictures (if included) before attempting installation.
- Check the parts and hardware packages against the parts list to assure that your kit is complete.
- Secure and properly rack the vehicle on a hoist prior to beginning installation.
- Always wear safety glasses when using power tools.
- Use extreme caution when cutting is required under the vehicle: the factory undercoating may be flammable. Be careful of all fuel lines, fuel tanks, brake lines, and electrical harnesses.
- When tightening bolts, foot-pound readings are listed on the Torque Specification Chart at the end of the instructions unless otherwise specified.

Installation # 8113

Kit Installation

- 1) If vehicle has an aluminum skid plate behind the front bumper that can be bolted back on without modifications, then you will not need this mounting kit. If the skid plate is plastic like in the following pictures, please proceed by cutting the skid plate as shown in Figure 1.




Figure 1: Make cut as shown, then trim to fit.

- 2) Drill out passenger side frame hole, using a 17/32 drill bit, to fit the 5/16 nutsert.
- 3) From HP9162, insert 5/16 nutsert in passenger & driver frame holes. Insert 1/4 nutsert in top middle frame hole. If you have a nutsert tool, use it to set the nutsert. If you do not have a nutsert tool, use the provided hardware and squish plate to set the nutsert. See Figure 2.

Installation # 8113




Figure 2: Insert 5/16 & 1/4 nutsert in the frame.

- 4) As shown in Figure 3, bolt the 8436 mounting bracket to the front cross member frame using 5/16 hardware on outer holes and 1/4 hardware on middle hole with tabs facing the front of the truck. As shown in Figure 4, put (3) 5/16 washers behind the passenger side bracket to space the bracket out far enough to clear the factory mounting plate.



Figure 3: Bolt bracket to frame



Figure 4: Space bracket using (3) 5/16 washers

- 5) Bolt the front of the skid plate to the factory location re-using factory hardware.
- 6) Align the back of the skid plate with the mounting bracket tabs and drill 5/16 holes through Skid plate. Bolt Skid plate to bracket tabs. See Figure 5.

Installation # 8113



Figure 5: Drill out and bolt the skid plate to the mounting bracket

Cognito Motorsports

Limited Lifetime Warranty

Cognito Motorsports warrants, to the original retail purchaser, that its suspension products are free from defects in workmanship and material for as long as the purchaser owns the vehicle on which the product was originally installed. Cognito Motorsports does not warrant the product for finish, alterations, modifications, and/or original installation contrary to specifications of Cognito Motorsports. Cognito Motorsports suspension products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities involving abnormal abuse other than the vehicle was originally designed to handle or endure. (A "RACE" is defined as any contest between two or more vehicles, and/or contest of one or more vehicle against the clock, whether or not such contest is for a prize.)

This warranty is for a one-time replacement of each Cognito Motorsports product and does not cover any part that Cognito Motorsports has previously replaced under this warranty. This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warrant are sales outside of the United States of America. Alterations to the finish of the parts including but not limited to painting, powder coating, plating, and/or welding will void all warranties. Cognito Motorsports obligation under this warranty is limited to the repair or replacement, at Cognito Motorsports option of the defective product. Any and all costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty.

This warranty excludes the following items: bushings, bumpstops, tie-rod ends, limiting straps, and heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days of purchase for defects in workmanship. Cognito Motorsports suspension components must be installed as a complete system. Any substitutions or exemptions of required components will immediately void the warranty. Some finish damage may happen to parts during shipping and is not covered under warranty. This warranty shall not apply to any product that had been subject to accident, negligence, alteration, abuse, or misuse. Cognito Motorsports does not warrant products not manufactured by Cognito Motorsports. Cognito Motorsports reserves the right to supersede, discontinue, or change the design, finish, part number and/or application of parts when deemed necessary by Cognito Motorsports without written notice, and in the sole and absolute discretion of Cognito Motorsports.

Warranty Claims

All warranty claims must be submitted through the original company of purchase. All claims must be shipped back to the original company of purchase with an approved RMA number listed as a reference on the shipping label and clearly printed on two opposing sides of the package(s); product in question must be inspected by Cognito Motorsports before replacement parts are shipped out.

Return Policy

Cognito Motorsports has a no refund return policy. Under special circumstances, returns might be accepted with prior written approval. All returned product will be shipped freight prepaid. Product returned is subject to a 25% restocking fee. No returns will be accepted after 30 days upon receipt of product.

Product Consumer Safety and Warning

The installation of this kit will modify the suspension of your vehicle and may cause it to handle significantly different than a factory equipped vehicle. Installing larger tires with modified suspension and increased ground clearance will significantly alter the handling characteristics of the vehicle, and may result in increased braking distances as well as changes in vehicle maneuverability and handling compared to the factory equipped vehicle. As with any vehicle, extreme caution and care must be used to prevent loss of control or roll-over during sharp turns or abrupt maneuvers. Always wear seat belts and drive safely, recognizing the reduced speeds and specialized driving techniques is required.

This suspension system will not strengthen nor reinforce the stock frame of the vehicle, nor will it increase rollover protection. It is necessary to periodically inspect all suspension and drive train components for tightness of fit or any damage. Installation of these parts will modify the height of the vehicle and will raise the center of gravity. Altered height modifications and off-road operation may increase your vehicle's susceptibility to roll over conditions and may cause serious injury or death. Many states regulate the height modification to each vehicle. Check the laws in your state for exact specifications. Height modifications may affect the reaction, ride, handling, and wear factor of your vehicle's components.

Failure to drive this vehicle safely may result in injury or death! Do not drive this vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications and combinations of modifications are not recommended, unsafe, and may not be permitted in your state. Consult your vehicle owner's manual, the instructions accompanying this product, and your state laws before undertaking these modifications. The owner of the modified vehicle and the qualified mechanic required to install this product are responsible for the legality and safety of the vehicle being modified.