JEEP TJ, YJ, XJ

- 1. When you remove original equipment steering stabilizer save 12 mm bolt and nut.
- 2. Assemble piston rod end of cylinder and pin kit as shown on poly bag 81131.
- 3. Place tapered end of pin kit into hole on tie rod. Install lock washer and nut hand tight.
- 4. Extend stabilizer to frame mount and install using original 12 mm bolt and nut. (See notes 8 & 9 at bottom.)

Jeep Grand Cherokee

- 1. When you remove original equipment steering stabilizer save 12 mm bolt and nut.
- 2. Install barrel end of stabilizer to frame mount using original 12 mm bolt and nut. (See notes 8 & 9 at bottom.)
- 3. Extend stabilizer to the tie rod mount. Using the kit bag with the bolt, washer and nut only, insert the provided sleeve into the bushing. Bolt cylinder to tie rod mount using the 10mm bolt, nut and washer provided.

GM

- 1. Remove plastic shield in front of cross member.
- 2. To remove original equipment you will find it easier if you have someone turn wheels until nut on tie rod mount of stabilizer cylinder is accessible.
- 3. When you remove original equipment steering stabilizer save 10 mm bolt and nut.
- 4. Assemble barrel end of cylinder and pin kit. Using sleeve that is already pressed into bushing.
- 5. Place tapered end of pin kit in hole on tie rod before installing bolt. Install lock washer and nut hand tight.
- 6. Install 10 mm sleeve into bushing.
- 7. Extend stabilizer to frame mount and install using original 10 mm bolt and nut.

IMPORTANT NOTES:

- 8. Tighten nuts securely on both ends of steering stabilizer
- 9. Turn wheels fully to right and left making sure that no interference occurs and that wheel stops are fully contacted.

BOX CONTENT

1 – Stabilizer cylinder 1 – Installation instruction sheet 1 –Pin kit 1 –Kit bag

CAUTION: Any and all warranties including but not limited to any express warranties, implied warranty of merchantability, or implied warranty of fitness for a particular purpose shall not apply to any product altered in any way outside the premises of the manufacturer or to any product which is not installed in accordance with the written instructions provided by the manufacturer for installation of the product.