



Silicone Hose Kit with Stainless Steel Clamps

2002-2004 GM 6.6L Duramax (LB7)
(115910204)

Installation Guide



DISCLAIMER OF LIABILITY

Performance products can increase horsepower above and beyond factory specifications. Additional horsepower creates more stress on the drive-train components, which could result in drive-train failure.

Note regarding emissions-related, non-E.O.-legal products: THESE PRODUCTS ARE LEGAL IN CALIFORNIA ONLY FOR RACING VEHICLES THAT MAY NEVER BE USED, OR REGISTERED OR LICENSED FOR HIGHWAY OR OFF-ROAD USE.

This agreement sets forth the terms and conditions for the use of PPE products. The installation of this product indicates that the Buyer has read and understands this agreement and accepts the terms and conditions. PPE (Pacific Performance Engineering) Inc., its distributors, employees, and dealers (the "Seller") shall not be responsible for the product's proper use and service. The buyer hereby waives all liability claims. The Buyer hereby acknowledges no reliance on the Seller's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof, and the Buyer hereby waives all remedies or liabilities expressed or implied, arising by law or otherwise (including without any obligation of the Seller with respect to fitness, merchantability and consequential damages), or whether or not occasioned by the Seller's negligence. The Seller disclaims any warranty and expressly disclaims any liability for personal injury or damages. The Buyer acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the Buyer agrees to indemnify the Seller and to hold the Seller harmless from any claim related to the item of equipment purchased. Under no circumstances will the Seller be liable for any damages or expenses by reason of use or sale of any such equipment. The Seller assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt, contact the manufacturer. The Buyer is solely responsible for all warranty issues from the manufacturer.

LIMITATION OF WARRANTY

The Seller gives Limited Warranty as to description, quality, merchantability, and fitness for a particular purpose, productiveness, or any other matter of Seller's product sold herewith. The Seller shall not be responsible for the products proper use and service and the Buyer hereby waives all rights other than those expressly written herein. This warranty shall not be extended, altered or varied except by a written instrument signed by Seller and Buyer.

Limited lifetime warranty on all PPE cast aluminum products, and PPE Transmission Coolers. Three (3) year limited warranty on PPE Manifolds and Up-Pipes Kits, and OEM-Length Up-Pipes. One (1) year limited warranty on all other PPE products from the date of sale to original buyer and limited solely to the parts contained within the products kit. All products that are in question of Warranty must be returned prepaid to the Seller and must be accompanied by a dated proof of purchase receipt. All Warranty claims are subject to approval by Seller. Under no circumstances will the Seller be liable for any labor charged or travel time incurred in diagnosis for defects, removal, or re-installation - of this product or any other contingent expenses. Under no circumstances will the Seller be liable for any damage or expenses incurred by reason of the use or sale of any such equipment. In the event that the buyer does not agree with this agreement: the buyer may promptly return this product, in a new and unused condition in its original packaging, with a dated proof of purchase to the place of purchase within ten (10) days from date of purchase for a full refund. The installation of this product indicates that the buyer has read and understands this agreement and accepts its terms and conditions.

INSTALLATION INSTRUCTIONS:

Step 1:

To gain access, the inner fender panel needs to be removed. A flat bladed screwdriver can be used to pry up the heads of the plastic fasteners.



Step 2:

With the inner fender out of the way, the lower driver side hose is accessible. A screwdriver is used to remove the clamps.



Step 3:

The stock hose may be hard to remove from the metal tubing. To ease removal, a 90-degree angled hook tool can be used to separate the hose from the metal tube.



Step 4:

Install the new PPE Performance Silicone Hose. Tighten the hose clamp to secure.



Step 5:

The cover is removed to gain access to the upper hose connection.



Step 6:

The upper connection is loosened and the hose clamp removed.



Step 7:

A long extension makes it easier to get to the lower clamp. That clamp is loosened.



Step 8:

Use a small 90-degree angled metal hook tool to separate the pieces. Remove the upper hose.



Step 9:

Before installing the new PPE silicone hose, make sure that the clamps are on and facing in a direction to make them easily accessible to tighten.



Step 10:

Remove the passenger side inner fender well. The lower passenger side hose clamps are then loosened.



Step 11:

Remove the stock hose.



Step 12:

With the clamps on loosely and oriented correctly, the lower hose is then installed.



Step 13:

Tighten clamps to secure.



Step 14:

The inner fender wells are reinstalled and the push fasteners are reinstalled.



Step 15:

Install and tighten second upper hose.

Installation complete.



