


304 Stainless Steel Cat-Back Exhaust Kit

2019-2024 RAM 1500 5.7L V8

(217050020, 217050030)

Installation Guide



CONTENTS

- A. (1) Inlet Pipe
- B. (1) Extension
- C. (1) Tube Hanger Clamp
- D. (1) Muffler
- E. (1) Drive Side Pipe, Front
- F. (1) Passenger Side Pipe, Front
- G. (1) Driver Side Exit Pipe
- H. (1) Passenger Side Exit Pipe
- I. (2) Rear Exit Pipe
- J. (2) 80 Degree Exit Pipe
- K. (2) Exhaust Tip
- L. (9) Clamp flat strap 3.0"

HARDWARE PACK

- M. (2) 3/8" Bolts
- N. (2) 3/8" Flat Washers
- O. (2) 3/8" Nuts
- P. (2) 90 Degree Exhaust Hanger

Trimming is required for certain wheelbase length, reference the following:


- For 154" wheelbase Crew Cab 6'4" Bed: No Cutting Required
- For 145" wheelbase Crew Cab 5'7" Bed: Trim 9" from extension tube B
- For 141" wheelbase Quad Cab 6'4" Bed: Trim 13" from extension tube B

DISASSEMBLY

1. Turn the vehicle off and allow time to cool down before installing.
2. Remove the two nuts securing the exhaust at the converter flange. (Fig. 1) Then, disconnect the flange at the muffler connection. (Fig. 2)



3. Remove the two studs from the converter flange. (Fig. 3)



4. Remove the tips from the resonators. (**Fig. 4, Fig. 5**)



Fig. 4



Fig. 5

5. Loosen the Y-pipe. (**Fig. 6**)



Fig. 6

6. Remove the passenger-side resonator from the Y-pipe, then remove the rubber hanger. (**Fig. 7**)



Fig. 7

7. On the driver-side, remove the ground strap from the frame and the exhaust. **(Fig. 8)**



Fig. 8

8. Remove the muffler from the hanger. **(Fig. 9)**




Fig. 9

9. Disconnect the driver-side resonator from the rubber hanger. **(Fig. 10)**
Then remove the resonator and muffler assembly from the vehicle.




Fig. 10

INSTALLATION:

1. Install the Inlet Pipe **(A)** using the following supplied hardware: two 3/8" bolts **(M)**, two 3/8" flat washers **(N)**, and two 3/8" nuts **(O)**. **(Fig. 11)**





Fig. 11

2. Install the Tube Hanger clamp (**C**) on Extension (**B**). (Fig. 12)
Depending on your chassis wheelbase, the Extension Tube (**B**) will need to be trimmed to the proper length.

**Fig. 12**


3. Slide one 3" clamp (**L**) over the Inlet Pipe (**A**), then install the Extension Tube (**B**). Next, secure Hanger Clamp (**C**) in the OEM rubber hanger.
4. Slide one 3" Clamp (**L**) over the Extension Tube (**B**), then install the Muffler (**D**). (Fig. 13)

**Fig. 13**

5. Install two 3" Clamps (**L**) over the muffler's exit flanges, then slide on the driver-side and passenger-side front pipes (**E**) and (**F**). (Fig. 14)
Secure both pipes to the factory hanger bracket. (Fig. 15)

**Fig. 14****Fig. 15**

6. Install the 90-degree exhaust hangers (O) onto the rear frame mounts, then install the driver-side and passenger-side exit pipes (G) and (H). Secure the pipes using two 3" Clamps (L) and reconnect the ground strap to the frame mount. (Fig. 16, Fig. 17)



7. Install either the Rear Exit Pipes (I) or the 80-degree Exit pipes (J), and secure them with two 3" Clamps (L). Then, install the 4" Exhaust Tips (K) (Fig. 18, Fig. 19).
8. Adjust the fitment of the exhaust system as needed, then tighten all Clamps (L), working from the front to the back of the vehicle.



Installation Complete

DISCLAIMER OF LIABILITY

Performance products can increase horsepower above and beyond factory specifications. Additional horsepower creates more stress on the drive-train components, which could result in drive-train failure.

Note regarding emissions-related, non-E.O.-legal products: THESE PRODUCTS ARE LEGAL IN CALIFORNIA ONLY FOR RACING VEHICLES THAT MAY NEVER BE USED, OR REGISTERED OR LICENSED FOR HIGHWAY OR OFF-ROAD USE.

This agreement sets forth the terms and conditions for the use of PPE products. The installation of this product indicates that the Buyer has read and understands this agreement and accepts the terms and conditions. PPE (Pacific Performance Engineering) Inc., its distributors, employees, and dealers (the "Seller") shall not be responsible for the product's proper use and service. The buyer hereby waives all liability claims. The Buyer hereby acknowledges no reliance on the Seller's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof, and the Buyer hereby waives all remedies or liabilities expressed or implied, arising by law or otherwise (including without any obligation of the Seller with respect to fitness, merchantability and consequential damages), or whether or not occasioned by the Seller's negligence. The Seller disclaims any warranty and expressly disclaims any liability for personal injury or damages. The Buyer acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the Buyer agrees to indemnify the Seller and to hold the Seller harmless from any claim related to the item of equipment purchased. Under no circumstances will the Seller be liable for any damages or expenses by reason of use or sale of any such equipment. The Seller assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt, contact the manufacturer. The Buyer is solely responsible for all warranty issues from the manufacturer.

LIMITATION OF WARRANTY

The Seller gives Limited Warranty as to description, quality, merchantability, and fitness for a particular purpose, productiveness, or any other matter of Seller's product sold herewith. The Seller shall not be responsible for the products proper use and service and the Buyer hereby waives all rights other than those expressly written herein. This warranty shall not be extended, altered or varied except by a written instrument signed by Seller and Buyer. The Warranty on PPE Manifolds and Up-Pipes Kits, OEM-Length Up-Pipes is three (3) years, a limited lifetime warranty on PPE cast aluminum pans and covers, and a limited lifetime warranty on PPE Transmission Coolers and one (1) year limited warranty on all other PPE products from the date of sale to original buyer and limited solely to the parts contained within the products kit. All products that are in question of Warranty must be returned prepaid to the Seller and must be accompanied by a dated proof of purchase receipt. All Warranty claims are subject to approval by Seller. Under no circumstances will the Seller be liable for any labor charged or travel time incurred in diagnosis for defects, removal, or re-installation - of this product or any other contingent expenses. Under no circumstances will the Seller be liable for any damage or expenses incurred by reason of the use or sale of any such equipment. In the event that the buyer does not agree with this agreement: the buyer may promptly return this product, in a new and unused condition in its original packaging, with a dated proof of purchase to the place of purchase within ten (10) days from date of purchase for a full refund. The installation of this product indicates that the buyer has read and understands this agreement and accepts its terms and conditions.

⚠ CA WARNING: Handling passenger or off-highway motor vehicle parts can expose you to chemicals such as phthalates and lead, which can cause cancer and reproductive harm. To minimize exposure, service the vehicle in a well-ventilated area, wear gloves, and wash your hands. For more information see www.P65Warnings.ca.gov/motor-vehicle-parts.



PACIFIC PERFORMANCE ENGINEERING

