



KRYPTONITE

KAWASAKI TERYX H2 COMPLETE RADIUS ROD KIT

****IMPORTANT****

Please read through these instructions thoroughly prior to installation. Failure to follow these steps may result in component or vehicle damage.

1. On a clean and level surface, raise the vehicle off the ground and support it appropriately. Once supported, remove the rear wheels.
2. Using a No. 3 Philips screwdriver, remove the plastic rock guards.
3. You will use a 17mm and 19mm wrench and sockets to loosen the radius rod and toe link hardware.
4. With all the hardware loosened, we're going to replace a single rod at a time, starting with the upper radius rod.
5. Match the Kryptonite Upper radius rod length to the OEM rod length then install it using the OEM washers and nuts. Hand tighten the nuts for now.
6. Next you will replace the lower radius arm, hand tighten the hardware once the Kryptonite Lower is installed.
7. Move onto the toe link ensuring you match the length of your Kryptonite toe link to the OEM link. Make sure the adjuster side is mounted on the trailing arm. Tighten the hardware, torque to **90 lb-ft**.
8. Moving back through the previous steps torque all your rod end hardware to **90 lb-ft**. Ensure the jam nuts are firmly snugged up. (snug + a quarter turn)



- Radius Rod Torque: **90 lb-ft**
- Adjustments: **Have the vehicle professionally aligned.**
- Rod End Jam Nuts: **Snug firm + A Quarter Turn.**



Register your parts
HERE



More information can
be found here

SACJ2492 WARNING: By installing this product, you acknowledge that the suspension of this vehicle has been modified. As a result, this vehicle may handle differently than factory-equipped vehicles. As with any vehicle, extreme care must be used to prevent loss of control or rollover during sharp turns or abrupt maneuvers. Always wear seat belts, and drive safely, recognizing that reduced speeds and specialized driving techniques may be required. Failure to drive this vehicle safely may result in serious injury or death. Do not drive this vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications (and combinations of modifications) are not recommended and may not be permitted in your state. Consult your owner's manual, the instructions accompanying this product, and state laws before undertaking these modifications. You are responsible for the legality and safety of the vehicle you modify using these components.

INSTALLATION ALIGNMENT NOTE: Your vehicle may require alignment after product installation. You may incur additional costs to align the vehicle.

INSTALLATION HEADLAMP AIM NOTE: In addition to your vehicle alignment, for your safety and others, it is necessary to check and adjust your vehicle headlamps for proper aim and alignment after product installation. You may incur additional costs to adjust the headlamp system.

INSTALLATION ADVANCED DRIVER ASSISTANCE SYSTEMS (ADAS) NOTE: If your vehicle is equipped with active or passive safety/collision monitoring and/or assistance/avoidance systems including, but not limited to, camera- or radar/sonar-based systems, check and adjust your vehicle's systems for proper aim and function after product installation. In some instances, your vehicle may require OEM dealer service tools and factory-trained technicians to recalibrate ADAS. You may incur additional costs to adjust ADAS systems.

 **FOLLOW US**
@kryptoniteproducts

KRYPTONITEPRODUCTS.COM